

Brings the invisible to light

Wireless inspection camera for systems up to 123 kV



Easy and quick inspections on switchgear installations – even on difficult to access parts



Facilitates work

The inspection camera makes regular inspections on medium-voltage and low-voltage installations easier: Difficult to access parts can be easily reached with the flexible operating head.

Saves time

The installation does not have to be disconnected during inspection. The state of the installation can be evaluated with the help of photos and films and measures can be discussed.



Increases safety

Photos of the installation are transmitted live from the inspection camera to a smartphone or tablet computer via radio link. This ensures that the electrician does not have to enter the live working zone.



Brings the invisible to light

The inspection camera allows the state of the installation to be monitored without great effort. Tools forgotten during maintenance work can be found with the help of photos and films.



Optional lighting
LED DIGIK ISO
Part No. 766 395



Brings light into the dark

Flexible working at any time, day or night, even in poorly illuminated environment. With the additional optional lighting you are independent of the lighting conditions.

Brings the invisible to light

Wireless inspection camera for systems up to 123 kV



Reliable inspection and easy operation via radio link to a smartphone or tablet


Wireless inspection camera is a complete set in a case

It consists of a camera with battery, USB cable, smartphone attachment, housing, adapter with gear coupling and transport case.

- For visual inspection of electrical installations with nominal voltages up to 123 kV / 15 to 60 Hz (without special training)
- Installation does not have to be disconnected
- For documentation of the state of the installation
- Wireless operation of the camera via smartphone or tablet computer
(System requirements: Android version 4.0-5.1 or iOS version 7.0-12.0)



SET DIGIK	Part No. 766 390
Standard	Based on EN 50508
Camera	18.2 megapixels Wide-angle lens with 10x optical zoom Optical image stabiliser Autofocus PlayMemories Home App Wi-Fi integrated Micro-USB 2.0 connection HD video recordings in MP4 format Temperature range: 0 °C ... +40 °C Material: Plastic
Dimensions of the case	395 x 290 x 105 mm

HG ZK 230	Part No. 766 393
	Handle*) with gear coupling up to 1000 V / 15 to 60 Hz and 1500 V / d.c.



More information on the camera and the accessories: de.hn/wic



*) Not included in delivery.

For information on our registered trademarks, please visit short link: de.hn/tm.
We accept no liability for technical modifications, misprints and errors. Illustrations are not binding.

DEHN + SÖHNE GmbH + Co.KG.
Tel.: +49 9181 906 0, info@dehn.de